



Metallic Graphite Blue (YLE)



Pearl Nebular Black (YAY)



Candy Sonoma Red (YHL)

Engine Type	4-stroke, liquid-cooled, DOHC, 4-cylinder	Wheels	Front	17M/C x MT3.50
Bore x Stroke	79.0 mm x 64.0 mm		Rear	17M/C x MT5.50
Displacement	1255 cm <sup>3</sup> (1255 cc)	Brakes	Front	Double disc brake
Compression Ratio	10.5 : 1		Rear	Disc brake
Ignition	Electronic ignition (Transistorized)	Tires	Front	120/70ZR17M/C (58W)
Starter System	Electric		Rear	180/55ZR17M/C (73W)
Lubrication System	Wet sump	Fuel Tank Capacity		19 L (5.0 US gal.)
Transmission	6-speed, return	Overall Length		2,130 mm (83.9 in.)
Primary Drive Ratio	83/54 (1.537)	Overall Width		790 mm (31.1 in.)
Final Drive Ratio	43/18 (2.388)	Overall Height	GSF1250	1,095 mm (43.1 in.)
Frame Type	Double-cradle (High-tensile steel)		GSF1250S	1,225 mm (48.2 in.)
Rake / Trail	25.2 degrees / 104 mm (4.1 in.)	Wheelbase		1,480 mm (58.3 in.)
Suspensions	Front 43mm telescopic forks, coil spring, oil damped, cartridge type, adjustable spring preload	Seat Height		790mm/810mm (31.1 / 31.9 in.) 2-way adjustable
	Rear Swingarm, link type, coil spring, oil damped, adjustable spring preload	Dry Weight	GSF1250 / A	222 kg (489 lbs.) / 226 kg (498 lbs.)
			GSF1250S / SA	225 kg (496 lbs.) / 229 kg (505 lbs.)

## FEATURES



Storage compartment



Grab bar and bungee hook



*Bandit*  
1250/1250S

